PARAMOUNT ARTS CENTER ASHLAND, KENTUCKY

TECHNICAL SUMMARY

This is an informational summary. It lists critical dimensions of the stage and the technical equipment currently in use in the buildings. It is intended for general information. If any data is especially critical, call to confirm that information.

THEATRE ADDRESS & MAIN CONTACTS:

Paramount Arts Center 1300 Winchester Ave. Ashland, KY 41101 (606) 324-0007 Fax (606) 324-1233 www.paramountartscenter.com

Holly Canfield - Executive Director David Miller- Marketing Director Nikki McGranahan – Artist Hospitality Adam Whaley (Studimo Productions) – Technical Director Mike Brown – Maintenance Technician Stage Hands - Local I.A.T.S.E. 369

Technical Services: Technical Director Adam Whaley Cell: 855-216-7199 adam@studimo.com Alternate Number:

Cell: (606)922-0380

John Griffiths

<u>Artist Hospitality</u> Nikki McGranahan

Phone: (606) 939-5470 nikki@paramountartscenter.com

Box Office Contact:

Allison Keesee (606)324-0007 <u>allison@paramountartscenter.com</u> Booking and Rentals: Holly Canfield Phone: (606)324-0007 ext.306 holly@paramountartscenter.com

Marketing David Miller 606-694-9784 david@paramountartscenter.com

INDEX

SUMMARY

- 1.0 STAGE
- 2.0 ORCHESTRA
- 3.0 FLOOR
- 4.0 LOADING DOCKS
- 5.0 SOFT GOODS/FLY SYSTEM
- 6.0 THEATRICAL LIGHTING SYSTEM
- 7.0 MONITOR SYSTEM
- 8.0 INTERCOM
- 9.0 MICROPHONES
- 10.0 FRONT of HOUSE AUDIO
- 11.0 RESTRICTIONS
- 12.0 LINE ROSTER
- 13.0 ORCHESTRA SHELL
- 14.0 RISERS, STANDS, ETC.
- 15.0 DRESS ROOM
- 16.0 WARDROBE ROOM
- **17.0 PRODUCTION OFFICE**
- 18.0 GENERAL AREA INFORMATION

SUMMARY

TYPE OF THEATRE: RENOVATED MOVIE THEATER WITH PROSCENIUM STAGE ADDITION- RESTORED IN 1972- RENOVATED IN 2001. SEATING 1417- 760 SEATS BALCONY & 657 SEATS MAIN FLOOR.

Handicapped Access

1 Wheelchair location Main Left Row BB- end seat

- 1 Wheelchair location Main Left Row C-- end seat
- 1 Wheelchair locations Main Right Row BB end seat

1 Wheelchair locations Main Right Row c - end seat

Wheelchair lift to Main Floor of theater

Handicapped accessible restroom, lobby, concession areas, backstage, and dressing rooms.

1.0 STAGE

Proscenium height: 24'11" Proscenium width: 58'0" Apron width: 58'0" Apron depth: 4'0" Plaster line to back wall: 47'0

2.0 ORCHESTRA

Dimensions of orchestra pit: 41 x 11 Seating capacity: 32 Pit cover: yes (available upon request) Access to pit: tunnel under stage Conductor chair: no Orchestra stands: available upon request Orchestra chairs: available upon request Piano: Baldwin Concert Grand

3.0 FLOOR

Floor:Sprung wooden floor (new 2001), blackRestrictions:Case hardened lagbolts onlyDance floor:Marley, black (available upon request)Offstage floor:Concrete

4.0 LOADING DOCKS

Dock 1 height:	36″
Distance from stage:	8'0"
Bay doors:	10' x 12'
Location:	Stage right

Dock 2 height:	36″
Distance from stage:	40'0"
Bay doors:	10' x 12'
Location:	Stage right

5.0 SOFT GOODS

Curtain Type:	Velour	
Legs:	(8) 14' x 26' black * see attached line roster	
Main Curtain:	Gold * see attached line roster	
Borders:	(2) 67' x 10' black * see attached line roster	
	(2) 67' x 4' black	
Cyc:	60' x 27' white	
Crossover:	Yes	

Type of Fly System:	T-BAR TRACK		
Location:	Stage left		
Number of line sets:	63 * see attached line roster		
Grid height:	55'		
Pipe diameter:	Schedule 80 (2")		
Pipe length:	67'0" feet		
Permanent flying uni	ts: Orchestral shell, back drops, movie screen *see line roster		

ŧ

6.0 THEATRICAL LIGHTING

Light Board:

	ETC Expression			
Fixtures: 300				
	8- 410 ETC Source Four 10 degree Ellipsoidals			
	110- 419 ETC Source Four 19 degree Ellipsoidals			
	60- 426 ETC Source Four 26 degree Ellipsoidals			
	30- 436 ETC Source Four 36 degree Ellipsoidals			
	24- 11411 Strand SL Zoom-variable focus 15/32 degree Ellipsoidals			
	40- 12181 Strand 8"Fresnelite			
	2- 26191 Strand Iris 4 Cyclight			
	7- 108-592 Colortran Cyc Strip			
	16- Source 4 Par (Med)			
Dimmers:				
	ETC Sensor dimmers - 192 1.8kw, 183 2.4kw			
Spots:	,			
·	2- LYCIAN 1290- 2000 Xenon			
Power:				
	400 Amp Disconnect (Lighting) located upstage left and upstage right.			
	200 Amp Disconnect (Audio) located Midstage right.			
	60 Amp Disconnect Rigging/Utility power.			
Front of House Coves				
	2 FOH coves house left 9 circuits each cove			
	2 FOH coves house right 9 circuits each cove			
Front of House Boom	-			
	2 booms house left 12 circuits			
	2 booms house right 12 circuits			
Stage Trees:				
U	10-3 circuit floor pockets			
	4-4 circuit floor pockets			
Proscenium Lighting:	•			
	5 electric rails with 168 patchable circuits. (See lineset schedule)			

Highsides: 20 circuits stage left; 20 circuits stage right

7.0 MONITOR SYSTEM +

Floor monitors:	6 (six) CLAIR BROTHERS AUDIO WEDGE A (3 mixes of power)
Drum fill sub:	1(one) CLAIR BROTHERS AUDIO ML-18
Monitor amps/proc:	4 (four) CLAIR BROTHERS AUDIO 2000Q
Sidefill cabinets:	2 CLAIR BROTHERS AUDIO R4111
Sidefill amplification:	LF- 1 CLAIR BROTHERS AUDIO CBX-1100
	MF- 1 CLAIR BROTHERS AUDIO CBX-900
	HF- 1 CLAIR BROTHERS AUDIO CBX-700

Sidefill crossover: BSS Mini Drive

8.0 INTERCOM

Intercom: 2 channel main station CLEAR COM MS232 6 belt packs CLEAR COM 6 headsets CLEAR COM 1 Stage manager station CLEAR COM

Assisted listening system: TELEX/SOUNDMATE

9.0 MICROPHONES +

Vocal mics:	6 SHURE BETA 58
Drum mics:	4 SHURE BETA 98
	1 SHURE BETA 52
	3 SHURE SM-81
Instrument mics:	8 SHURE SM-57
Wireless mics:	1 AT2000 handheld
Floor mics:	3 CROWN PCC 160
Direct boxes:	5 COUNTRYMAN TYPE 85

10.0 FRONT OF HOUSE AUDIO

House Line Array:	 (8) per side Clair Brothers i208 (2) per side Clair Brothers CS218 LAB Gruppen PLM/FP series power amps with Lake Processor 		
House PA:			
Center cluster:	(4) CLAIR BROTHERS	AUDIO R2T	
Delay system:	(4) CLAIR BROTHERS	AUDIO R2DNH	
Front fills:	(8) PAS PB100B		
Amplification:	Center Cluster:	Lows-1 CLAIR BROTHERS AUDIO CBX 900	
		Highs- 1 CLAIR BROTHERS AUDIO CBX 700	
	Delay system:	Lows- 1 CLAIR BROTHERS AUDIO CBX 90	
		Highs- 1 CLAIR BROTHERS AUDIO CBX 700	
	Front Fills:	2 CLAIR BROTHERS AUDIO CBX 700	
Processing and Equalization:		Dolby Lake	
Snake: 48 Channel 3 way ISC		DLATED	

Console: Midas M32

11.0 RESTRICTIONS

Maximum db not to exceed 98dB SPL A weight average at FOH

12.0 LINESET SCHEDULE

12.0	LINESEI	SCHEDULE			
LINE	US OF PL	PURPOSE	WEIGHT LBS	SIZE	NOTES
0	1'4"	FIRE CURTAIN		61'2-1/2 X 26'11"	
1	1'8"	GRAND VALANCE	1500	67'0" X 12'0"	
2	2'4"	GRAND DRAPE	2400	2/35'0" X 26'0"	
3	3'0"	OPEN	1500		
4	3'8"	OPEN	1500		
5	4'4"	1 st ELECTRIC	2400		42 CIRCUITS
	5'0"	OPEN	1500		42 CINCOTTS
6					
7	5'8"	OPEN	1500		
8	6'4"	ORCHESTRA SHELL	2400		CAN NOT BE REMOVED
9	7'0"		1500		
10	7'8"		1500		
11	8'4"	1 ST BORDER	1500	67'0" X 3'0"	
12	9'0"	1 st LEG	1500	2/14'0" X 26'0"	
13	9'8"		1500		
14	10'4"	2 ND ELECTRIC	2400		32 CIRCUITS
15	11'0"		1500		
16	11'8″		1500		
17	12'4"		1500		
18	13'0"		2400		
18	13'8"		1500	67'0" X 26'0"	+
		INTERMISSION CURTAIN		07U X 20U	
20	14'4"		1500		
21	15'0"		1500		
22	15'8″	ORCHESTRA SHELL	2400		CAN NOT BE REMOVED
23	16'4"	2 ND BORDER	1500	67'0" X 3'0"	
24	17'0"	2 ND LEGS	1500	2/14'0" X 26'0"	
25	17'8″		1500		
26	18'4"	3 RD ELECTRIC	2400		32 CIRCUITS
27	19'0"		1500		
28	19'8″		1500		
29	20'4"		1500		
30	21'0"		1500		
31	21'8"		1500		
32	22'4"		1500		
33	22'4		1500		
	23'8"				
34		3 RD BORDER	1500	67'0" X 10'0"	
35	24'4"	3 RD LEGS	1500	2/14'0" X 26'0"	
36	25'0	ORCHESTRA SHELL	2400	67'0" X 10'0"	CAN NOT BE REMOVED
37	25'8"		1500		
38	26'4"	4 th ELECTRIC	2400		30 CIRCUITS
39	27'0"		1500		
40	27'8″		1500		
41	28'4"		1500		
42	29'0"		1500		
43	29'8"		1500		
44	30'4"		1500		
45	31'8"	4 [™] BORDER	1500	67'0" X 10'0"	1
46	32'4"	4 TH LEGS	1500	2/14'0" X 26'0"	
47	33'0"	ORCHESTRA SHELL	1500	67'0" X 10'0"	CAN NOT BE REMOVED
47	33'8"		1000		
48	34'4"	5 TH ELECTRIC	2400	+	32 CIRCUITS
					JZ CINCUITS
50	35'0"	OPEN	1500		
51	35'8"	OPEN	1500		
52	36'4"	OPEN	1500	67'0" X 10'0"	
53	37'0"	OPEN	1500		
54	37'8"	OBSTRUCTED- 6 TH ELECTRIC	2400		28 CIRCUITS
		REAR WALL ORCH SHELL	3800		CAN NOT BE REMOVED
55	38'4"	OPEN	1500		
56	39'0"	OPEN	1500	1	
57	39'8"	SCRIM	1500		1
ı	-	1		1	1

58	40'4"	REAR CURTAIN	2400	2/35'0' X 26'0"	
	41′0″	59-63 ORCHESTRA SHELL	SIDEWALL	STORAGE	CAN NOT BE REMOVED
60	41′8″				

13.0 WENGER DIVA ORCHESTRA SHELL

26 ETC Source Four PARs patched into house dimming system

14.0 RISERS, STANDS, ETC.

8 - 4'x8' Wenger risers – please advance heights

16 Music Stands with lights

Full complement of microphone stands

15.0 DRESSING ROOMS

- 2 Chorus Room: 15-20 person occupancy
- 1 Cast Room: 5-9 person occupancy
- 1 Star Room: 3-5 person occupancy
- 1 Star room: 1-2 person occupancy

Paging System available from Stage to Dressing Room Area.

16.0 WARDROBE ROOM

2 Heavy Duty Washers/Dryers2 Steamer2 Iron Board/IronsPaging System available from Stage to Wardrobe Room Area.

17.0 PRODUCTION OFFICE

One phone line No fax Line Internet Connection Paging System available from Stage to Production Office Area.

18.0 GENERAL INFORMATION

Hotels in vicinity:

Marriott Delta 1441 Winchester Ave, Ashland, KY 41101 +16063271100

Quality Inn 4708 Winchester Avenue (623)209-7607

Holiday Inn Express & Suits 13131 Slone Court (606) 929-1720

Days Inn by Wyndham Ashland

12700 KY-180 (606)928-3600

Fairfield Inn by Marriott

10945 U.S. 60 (606) 928-1222

Hampton Inn

1321 Cannonsburg Road (606) 928-2888 or (800) HAMPTON

Local Restaurants

(Within walking distance)

BELLA FONTE RESTAURANT

1320 Carter Ave......606/920-7682

BOB EVANS RESTAURANT

1224 Carter Ave	606/324-1600
BURGER KING	
1200 Winchester Ave	606/928-6927
FAT PATTY'S	
144 Winchester Ave	606/325-7287
STARBUCKS	
1201 Winchester Ave	606/329-0010

Local Restaurants with Catering

Bellefonte Country Club

208 Country Club Drive Ashland, KY 41101 (606) 324-2107

Chick-fil-A

410 River Hill Dr. Ashland, KY 41101 (606) 324-7469

Texas Roadhouse

501 Winchester Ave Ashland, KY 41101 (606) 325-5188

Area Hospitals

Kings Daughters' Medical Center

Lexington Avenue......606/408-4000

Parking

<u>CREW AND ARTISTS</u>: Trucks and buses may remain parked in loading dock as space allows. Supplemental parking is available on street or in lot east of theater.

PUBLIC: On street Parking.

Travel Directions

The Paramount Arts Center is located in downtown Ashland, KY at 1300 Winchester Avenue, the main thoroughfare of the city.

FROM LEXINGTON, KY (traveling east)- From I-64, take exit 191 to US 23 North. Turn left from the exit.

FROM CHARLESTON, WV (traveling west)- From I-64, take exit 191 to US 23 North. Turn right from the exit.

Once on US 23, continue several miles passing through the city limits of Catlettsburg, KY and then entering Ashland.

After passing by the "Welcome to Ashland" sign, located on your right, continue straight through the intersection.

At this point US 23 turns into Winchester Avenue.

The theater is located at 13th Street and Winchester Avenue just a few miles on the left.

From US 52 in Ohio, cross the bridge from Ohio into Ashland, KY.

At traffic light make a left and the theater is one block on your right.